

Remote Sensing Thermostat

- Rain Tight
- Temperature Control
- NEMA 4X
- Line Sensing



Features

- Rugged weather resistant enclosure made of corrosion resistant materials for long life.
- Stainless steel remote bulb provides rapid response to temperature change.
- Large, readily visible dial with 0°F - 120°F temperature range.
- Multi-positional mounting offers flexibility in either new or existing installations.
- One control for both heating and cooling applications.

Description

The WS-115R thermostat is designed for use as a line sensing control for pipes, vessels and other types of electric heat tracing applications. Suitable in agricultural, industrial and commercial environments.





Remote Sensing Thermostat

Characteristics

Type	Range	Differential	Bulb Size	Capillary Length	Shipping Weight
SPDT	0°F - 120°F	3°F	2 5/16" x 5/16"	5 Feet	1.0 Lbs

Mechanical Data

⚠ Electrical Ratings				
	120VAC	240VAC	277VAC	480VAC
Full Load Amps	16.0	12.0	10.0	—
Locked Rotor Amps	80.0	60.0	50.0	—
Non-Inductive Resistive Load Amps	25.0	25.0	22.0	5.0

Installation

- Multi-positional mounting meets new or existing wiring needs.
- Insulated enclosure.
- All mounting holes are exterior to the enclosure.
- Easily removable knockouts in sides and top of enclosure.
- Large wiring compartment with watertight cover separated from thermostat compartment.
- May be cord or conduit connected.
- Pigtail leads for rapid, positive, electrical connection.

Applications

- Constant Wattage Heater Cables
- Self Limiting Heater Cables
- Mineral Insulated Heater Cables

