

EcoTrace Sequencing Panels Data Sheet

GENERAL PRODUCT INFORMATION

Double the square footage covered or cut your operating cost in half with these EcoTrace Sequencing Control Panels. The sequencing panels are designed to rapidly switch the power between two zones to heat all of the surface area using half the amperage. The panel can be activated by an in-ground sensor, aerial-mount sensor, manual start button, or WiFi.



FEATURES INCLUDE:

- Significant power saving reduces operating costs
- Melt more snow with the available power
- Proprietary software manages the inputs and outputs to sequence the zones and panels
- Weatherproof panel enclosures
- Ground fault transducer 0-100 milliamps
- Manual 4 hours start/stop button
- Pre-wired terminal connections
- Solid state relays; operates silently
- Internal fan keeps components cool
- Fast acting fuses provide overcurrent protection
- LCD status display
- 2-year limited warranty

TECHNICAL DATA

Input Voltage Range:	1Ø 240VAC, 3Ø 208VAC, 3Ø 480VAC
Enclosure Type:	Outdoor rated weatherproof enclosure
Fuse Type:	Class CC current limiting, fast-acting fuses provide overcurrent protection
Relay Type:	Solid State Relays
Dimensions (H x W x D):	
Modular Sequence Control Panel	16 x 12 x 6-inches (406mm x 305mm x 152mm)
Small Power Panel (240V)	36 x 24 x 8-inches (914mm x 610mm x 203mm)
Small Power Panel (208V 480V)	36 x 36 x 8-inches (914mm x 914mm x 203mm)
Large Power Panel (240V)	36 x 36 x 8-inches (914mm x 914mm x 203mm)
Large Power Panel (208V & 480V)	60 x 36 x 8-inches (1,524mm x 914mm x 203mm)
Approvals	UL listed in the U.S. and Canada

IMPORTANT NOTE: Maintain a clearance of 8-inches on both sides of the sequencing panel.

Insulation is usually recommended because it can improve the efficiency and lower the operating cost of your system. Consult with your contractor. (*NEVER place the heat cable directly on top of the insulation.*)

TECHNICAL SUPPORT

For technical questions, please contact ProLine at 866.676.WARM (9276) or visit www.prolineradiant.com.



ProLine Radiant accepts no responsibility for possible errors in catalogs, brochures, other printed materials, and website information. ProLine reserves the right to alter its products without notice. This also applies to products already on order provided that such alteration can be made without subsequent changes being necessary in specifications already agreed upon. All trademarks in this material are property of the respective companies. All rights reserved.